



Model weight: **27 gr**



Units per box: **10**

**NEUTRAL**



1095.D6  
**Soldadura  
DIN6**



1095.D3  
**Soldadura  
DIN3**



1095.D4  
**Soldadura  
DIN4**



1095.D5  
**Soldadura  
DIN5**



1095.D7  
**Soldadura  
DIN7**

**GRADUATED**



1095.01  
**Soldadura  
DIN5**



1095.02  
**Soldadura  
DIN3**



1095.03  
**Soldadura  
DIN4**



1095.04  
**Soldadura  
DIN6**



1095.05  
**Soldadura  
DIN7**

**NEUTRAL**

REF.	DESCRIPTION	FRAME MARKING	LENS MATERIAL AND MARKING	COATING
1095.D6	Soldadura DIN6	Ⓜ EN175F <b>CE</b>	Polycarbonato 2C-1.2 Ⓜ 1F <b>CE</b> / 6 Ⓜ 1F <b>CE</b>	Antiraya - Antivaho
1095.D3	Soldadura DIN3	Ⓜ EN175F <b>CE</b>	Polycarbonato 2C-1.2 Ⓜ 1F <b>CE</b> / 3 Ⓜ 1F <b>CE</b>	Antiraya - Antivaho
1095.D4	Soldadura DIN4	Ⓜ EN175F <b>CE</b>	Polycarbonato 2C-1.2 Ⓜ 1F <b>CE</b> / 4 Ⓜ 1F <b>CE</b>	Antiraya - Antivaho
1095.D5	Soldadura DIN5	Ⓜ EN175F <b>CE</b>	Polycarbonato 2C-1.2 Ⓜ 1F <b>CE</b> / 5 Ⓜ 1F <b>CE</b>	Antiraya - Antivaho
1095.D7	Soldadura DIN7	Ⓜ EN175F <b>CE</b>	Polycarbonato 2C-1.2 Ⓜ 1F <b>CE</b> / 7 Ⓜ 1F <b>CE</b>	Antiraya - Antivaho

**CUSTOM PRESCRIPTION**

- We have an optical service close to the workplace to take prescriptions. Online management platform. Delivery time: 5 working days.

REF.	FRAME	SIZE	FRAME MARKING	LENS MATERIAL	LENS MARKING	PRESCRIPTION LIMIT	COATING
1095.01	Soldadura DIN5	54	Ⓜ EN175F <b>CE</b>	CR-39 1.5	Ⓜ 1S <b>CE</b>	+8,-8	- Antiraya - Blue Stop
1095.02	Soldadura DIN3	54	Ⓜ EN175F <b>CE</b>	Polycarbonato	Ⓜ 1F <b>CE</b>	+8,-8	
1095.03	Soldadura DIN4	54	Ⓜ EN175F <b>CE</b>	CR-39 1.6 (MR-8)	Ⓜ 1S <b>CE</b>	+8,-10	
1095.04	Soldadura DIN6	54	Ⓜ EN175F <b>CE</b>	Mineral	Ⓜ 1S <b>CE</b>	+7,-7	
1095.05	Soldadura DIN7	54	Ⓜ EN175F <b>CE</b>				

**MARK MEANING **CE****

Symbol	Rule	Description
Ⓜ	<b>EN166:2001</b>	Identification of OPTOR S.A.U.
<b>1</b>	<b>EN166:2001</b>	Optical class symbol.
<b>F</b>	<b>EN166:2001</b>	Contra partículas a alta velocidad, baja energía. Resiste al impacto de una bola de acero de 6mm de diámetro y de 0,86g a 45 m/s.
<b>2C-1.2</b>	<b>EN170:2002</b>	Filtro Ultravioleta EN170
<b>6</b>	<b>EN175:1997</b>	EN175 Filtro Soldadura Din 6
<b>3</b>	<b>EN166:2001</b>	EN175 Filtro Soldadura Din 3
<b>4</b>	<b>EN166:2001</b>	EN175 Filtro Soldadura Din 4
<b>5</b>	<b>EN166:2001</b>	EN175 Filtro Soldadura Din 5
<b>7</b>	<b>EN175:1997</b>	EN175 Filtro Soldadura Din 7

Symbol	Rule	Description
S	EN166:2001	Resistencia mecánica incrementada (6 m/s)
CE		European regulations.



Certificate No. AC07096 Rev.1  
No. notified body 0530



## DECLARATION OF CONFORMITY CE

In accordance with the Union harmonization legislation applicable to Regulation (EU) 2016/425

### The manufacturer

OPTOR S.A.U.  
C/Quintana i Millars, 2, naveG  
08940 Cornellà de Llobregat  
Barcelona (SPAIN)

Declares under its sole responsibility that the category II PPE described below is in accordance with the EU harmonization legislation applicable to Regulation (EU) 2016/425 and with the harmonization standards related in the table below.

MOD. DUPLEX			
REF.	DESCRIPTION	HARMONIZED STANDARDS	LABORATORY
1095.01	DUPLEX Soldadura DIN5	EN166:2001 - EN170:2002 - EN175:1997	Certottica
1095.02	DUPLEX Soldadura DIN3	EN166:2001 - EN170:2002 - EN175:1997	Certottica
1095.03	DUPLEX Soldadura DIN4	EN166:2001 - EN170:2002 - EN175:1997	Certottica
1095.04	DUPLEX Soldadura DIN6	EN166:2001 - EN170:2002 - EN175:1997	Certottica
1095.05	DUPLEX Soldadura DIN7	EN166:2001 - EN170:2002 - EN175:1997	Certottica
1095.D6	DUPLEX Soldadura DIN6	EN166:2001 - EN170:2002 - EN175:1997	Certottica
1095.D3	DUPLEX Soldadura DIN3	EN166:2001 - EN170:2002 - EN175:1997	Certottica
1095.D4	DUPLEX Soldadura DIN4	EN166:2001 - EN170:2002 - EN175:1997	Certottica
1095.D5	DUPLEX Soldadura DIN5	EN166:2001 - EN170:2002 - EN175:1997	Certottica
1095.D7	DUPLEX Soldadura DIN7	EN166:2001 - EN170:2002 - EN175:1997	Certottica

The PPE subject to this declaration is identical to the one that has been submitted to the EU Type examination.

CERTIFICATE CE Nº	ISSUED BY	NO. NOTIFIED BODY	CERTIFICATE DATE	VALID UNTIL
AC07096 Rev.1	Certottica	0530	04/10/2019	03/10/2024

